SUPERIOR
TOOL RENTAL & REPAIR

BTB 400A MIG Gun w/ Large Curved Handle

SPECIFICATIONS

Item #	**BTB**
Process	MIG (GMAW)
Rated Output	400 A
Duty Cycle	100% CO2 Gas, 60% w/ Mixed Gases
Wire Size Ranges	.023" to 1/8"
Neck	Rotatable, no tools required to change rotatable necks
Cable Length	15 ft industrial grade cable

PipeWorx MIG Gun

SPECIFICATIONS

Item #	**Included with Rental of ArcReach Smart Feed Item # 951733 Manufacturer Part #195400**				
Neck	60-degree neck w/ tapered tip and nozzle for excellent visibility on root passes and pipe joints. Standard tip & nozzle for fill & cap				
Centerfire™ Tip	Provides "drop-in" tip with no threads. Quick changeover. No tools required.				
Cable Length	15 ft				
Weight	10 lbs				
Gas and Duty Cycle Specifications	**Gas Type**	**100% Duty Cycle**	**100% Duty Cycle CE**	**60% Duty Cycle CE**	**35% Duty Cycle CE**
	CO_2 Gas	350 A	320 A	370 A	470 A
	80% Argon 20% CO_2 Gas	—	270 A	310 A	390 A

Magnum® Classic MIG Gun, Semiautomatic

SPECIFICATIONS

Item #	**K126-2 Classic**
Process	Flux-Cored Self-Shielded
Rated Amps @ 60% Duty Cycle	350 Amps
Cable Length	15' Industrial Grade
Wire Diameters	.062" to 3/32"
Gun Tube Angle	62°

Magnum® PRO Curve™ Welding Gun, Semiautomatic

SPECIFICATIONS

Item #	**K2952-2**
Process	Flux-Cored (FCAW), MIG (GMAW), Pulsed MIG (GMAW-P)
Rated Amps @ 60% Duty Cycle	**CO2:** 400 A **Mixed:** 400 A @ 50% DC
Wire Diameters	.025" to 5/64"
Cable Length	15 ft

Spoolmatic® Pro Air-Cooled Spool Gun, Pistol-Grip

SPECIFICATIONS

Item #	**301148**
Processes	MIG (GMAW), Pulsed MIG (GMAW-P) (with pulsing source)
Wire Types	Aluminum, steel
Rated Output	200 A at 100% duty cycle
Wire Feed Speed	70–900 ipm (dependent on control box or Millermatic used)
Wire Diameter Capacity	**Aluminum:** .030–1-1/16" **Hard Wire:** .030–0.45"
Max. Spool Size Capacity	4"
Included	WC-24 weld control (137 549) push-pull advanced gooseneck
Dim. / Net Weight	**H** 10.75" **W** 2.5" **L** 15.375" **/ Gun with 30-ft. Cable** 15.7 lbs

Python 225A Air Cooled MIG Push/Pull Gun

SPECIFICATIONS

Item #	**232-825**
Weldable Metals	Aluminum, flux cored wires, steel
Cooling Mechanism	Air Cooled
Barrel Specs	6" Gooseneck, Ez-lock barrel can rotate 360°
Rated Output	225 A at 100%
Wire Feed Speed	800 ipm
Snake Skin Length	25 ft
Wire Type & Diameter	**Aluminum and Cored Wire:** 0.030" - 1/16" **Solid and Hard Wire:** 0.030" - 0.045"
Compatibility	Miller, Lincoln and Frontius feeders

Call to Order
877.446.4352

LOCATIONS
Greater Detroit
Greater Chicago
Greater St. Louis

GO ONLINE
www.**midlandtool**.com
www. **superiortoolrental**.com

GET SOCIAL